
Product Specification

Description	LED Amusement Lamp
Model NO	YJ-S5054RGB-1.5W

Product Picture




Part Number	Chip Emitt Material Col	_	Forwardvoltage		Dominant Wavelength		Luminous Intensity(Lm)		IF(mA)	Viewing Angle_
		Color	TYP	MAX	MIN	MAX	MIN	MAX		Δθ
YJ-S5054RGB-1.5W	AlGaInP	Red	1.8	2.4	620	635	8	15	150	120
	GAN	Green	2.8	3.6	515	525	25	45	150	120
	GAN	Blue	2. 8	3.6	455	475	6	12	150	120


PRODUCT SIZE

















PackageDimensionsmm GeneralTolerance02



SHENZHEN AGLARE LIGHTING CO., LTD
Web: www. aglare.cn/www. amusementlamp.com

Email: aglare@aglare. cn

Tel: +86-75588868631



Instructions:

K=K Material Carton Electrostatic bag

Customer information

Please read the specification before used:

Products dehumidification

Because the SMD product moisture absorption in high temperature welding will cause water vaper evaporation and expansion. Easy to cause disengagement. It is easy to pull the chip from the gold wire. Therefore, before use, customers should bake at 60-70 degrees

centigrade.for 12hours before unpacking.welding should be finished within 24 hours after

unpacking. If more than 24 hours need to do dehumidification again. (Bake the beads in the coil at 65-75 degrees Celsius for 10 - 15 hours, Bulk baking: 130-150 degrees Celsius for 2-3 hours)

SMT

Customers in the SMT patch as far as possible to choose a large than SMD light surface nozzle, to prevent the nozzle down the height of the improper setting of the lamp caused by damage to the inner gold line, SMT nozzle down the height will also affect the quality of the lamp.

Anti-static precautions

The machine in contact with the product during use should be grounded by wire. The soldering iron of the working table must be grounded.

The operator must wear an esd ring and esd suit.



Web: www. aglare.cn/www. amusementlamp.com

Email: aglare@aglare. cn Tel: +86-75588868631